

# OPTIONS and SPECIFICATIONS

| Model   | 1100        | 1300        | 1600           | 2000      |
|---|-------------|-------------|----------------|-----------|
| 900/60 R32 Lug High Flotation Tires   | i           | n/a         | n/a            | n/a       |
| Goodyear 1100/45R46 LSW   | o           | n/a         | n/a            | n/a       |
| Goodyear 1250/40R46 LSW   | o           | i           | n/a            | n/a       |
| Goodyear 1400/30R46 LSW   | o           | o           | n/a            | n/a       |
| Transfer Track (36" x 140")   | o           | o           | n/a            | n/a       |
| Large Track (36" x 170")  | n/a         | o           | i              | i         |
| Brakes (Hydraulic)  | o           | o           | o              | o         |
| 5 Point Scale   | o           | o           | i              | i         |
| Haulmaster Connect Scale Indicator<br><small>(Includes Tablet and Mount)</small>                | o           | o           | o              | o         |
| Haulmaster Pro  | o           | o           | o              | o         |
| Agrimatics Scale Indicator  | o           | o           | o              | o         |
| DigiStar GT560 Scale Indicator  | o           | o           | o              | o         |
| Manual Roll Tarp  | o           | o           | o              | o         |
| Electric Roll Tarp w/Switch   | o           | o           | o              | o         |
| Hydraulic Auger Drive   | o           | o           | n/a            | n/a       |
| Pivoting Auger  | i           | i           | i              | i         |
| 2 Camera Ag Cam w/9" Display  | o           | o           | o              | o         |
| Hydraulic Jack <small>(additional hydraulic circuit required)</small>                           | o           | o           | o              | o         |
| Track Mud Scrapers  | o           | o           | o              | o         |
| Tow Hitch   | o           | o           | o              | o         |
| Width   | 12' 1"      | 12' 1"      | 13' 11"        | 13' 11"   |
| Overall Length  | 32' 2"      | 32' 2"      | 37' 3"         | 37' 3"    |
| Tank Length   | 22' 6"      | 22' 6"      | 28' 3"         | 28' 3"    |
| Loading Side Height   | 10' 1"      | 11' 1"      | 10' 4"         | 11' 3"    |
| Transport Height  | 11' 4" 1    | 12' 4" 1    | 11' 8"         | 12' 7"    |
| Auger Max Height  | 16'         | 16'         | 17' 2"         | 17' 2"    |
| Auger Max Reach   | 10' 6"      | 10' 6"      | 10' 11"        | 10' 11"   |
| Empty Weight  | 24,350lbs 1 | 24,650lbs 1 | 30,300lbs      | 30,675lbs |
| Tongue Weight   | 3,800 lbs   | 3,800 lbs   | 4,200 lbs      | 4,200 lbs |
| Standard Tire/Wheel   | 900/60 R32  | 1250/40R46  | 36"x170" Track |           |
| Unloading Auger   | 22"         | 22"         | 24"            | 24"       |
| Horizontal Auger  | 22"         | 22"         | 22"            | 22"       |
| Hydraulic Remotes 2   | 4           | 4           | 4              | 4         |
| Req Tractor HP (Kw)   | 200 (150)   | 275 (200)   | 350 (260)      | 400 (300) |
| 1 With Transfer Track 2 Haulmaster Pro Reduce To 1 Remote, Optional Hydraulic Jack Add 1 Remote |             |             |                |           |
| o - optional   i - included   |             |             |                |           |



# HAULMASTER

Right and Left Hand Auger Available



ELMERSMFG.COM

f i t YouTube #HAULMASTER



# POWERMASTER

Custom Designed Direct Drive Gearbox

Custom designed (patent pending) direct drive gearbox eliminates belts while increasing throughput efficiency.

- Allows cart to be up to 16" lower than previous models.
- Reduces maintenance.
- Improves grain flow efficiency.
- Increases auger output capacity at the same horsepower.
- Manual horizontal auger disconnect if necessary.

## INDUSTRY LEADING DESIGN TO MAXIMIZE YOUR HARVEST

- Increased Combine Auger Clearance Up To 16"
- 17ft Auger Spout Clearance with 30 Degree Auger Pivot Range
- Full Length Horizontal Auger Cleanout
- Low-Maintenance Oil Bath Hubs
- Fully Welded Undercarriages
- Clean and Efficient Wiring with Grommets and High Quality Connectors
- Large See Through Windows
- Custom Tarp System
- Bolt Together Design
- Dynamically Balanced Auger Within 1 oz.

## HAULMASTER PRO



Smart and simple hydraulic system giving the operator advanced, patent pending, tools to be faster and more efficient.

- Industry exclusive double tap to auger fold/unfold.
- Industry leading auger fold/unfold speed.
- Auto spout return home on fold.
- Comfortable joystick control for gate, pivot, fold and spout.
- 4-way spout control with double axis proportional joystick.
- Auto gate close for specific truck weight.
- Gate auto close option at 3 MPH.
- Virtual joystick option on tablet
- Includes HAULMASTER CONNECT.
- Simple connection, uses 1 hydraulic remote and standard 7 pin plug.

## NEW FOR 2019

- Improved Frame Design.
- Custom Tarp System.
- LED Marker Lights.
- Improved Auger Hinge.
- 4 Way Spout Control.
- Toolbox Standard.
- Increased Tire Options.
- Tow Hitch Option.
- Improved Auger Drive Lug.
- POWERMASTER Gearbox.
- HAULMASTER CONNECT.
- HAULMASTER PRO.

# AVAILABLE SIZES

1100 • 1300 • 1600 • 2000

## HAULMASTER CONNECT

Smart interface to interact with your HAULMASTER features.

- Detailed Load Tracking
- Information stored on Controller, not tablet.
- Export load data to email.
- GPS load tagging.
- No Battery required.
- Integrated sensors.
- Multiple tablets possible.
- Turn Key Package.

